"THE HEART AND SOUL OF INFECTION CONTROL" TM



Enviropouch Instructions for Use (IFU)

- 1) Clean all instruments thoroughly by soaking in a neutral pH detergent solution, hand scrubbing, or clean in an ultrasonic cleaner.
- 2) Place cleaned instruments & cassettes in Enviropouch, invert the cuff or fold the inseam, and seal cuff or flap, respectively, with steam process indicator tape in vertical direction.

P.O. Box 2295 308 D-Bob Industrial Drive Suite 3 Peachtree City, GA 30269

- 3) Always insert an indicator to show exposure to the sterilization process.
- 4) Sterilize in a steam autoclave at 250 F 16 to 18 psi for 20 minutes or 270 F 30 psi for 5 minutes. Follow steam autoclave manufacturer directions.

Phone: (877) 770.632.1991 Fax: 770.742.0224

- 5) Remove the Enviropouch immediately to air dry or machine dry on low heat.
- 6) Remove the autoclave indicator tape in downward direction, from the top of the vertically sealed cuff or flap.



Enviropouch is **launder-free**, reuseable in the steam autoclave process with **no laundering necessary**.

Enviropouch has useful life of 200 sterilization cycles.

y

Storage conditions require normal ambient conditions.

Check us out! WWW.ENVIROPOUCH.COM